

# CONTACT CLEANER

HIGH QUALITY CONTACT CLEANER

## Description

Rymax Contact Cleaner is recommended for the removal of light oils, dust, dirt and fingerprints from electrical connectors, printed circuit boards, relays, switches, scales, timers and other sensitive electrical and electronic equipment.

## Applications

- Switches
- Batteries
- Contact Points
- Printed Circuit Board Switches
- Multiple Sockets

## How to use?

Before use, carefully read the directions on the packaging and act accordingly. The aerosol should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol.

Switch off electrical installations before treatment. Spray the parts to be treated until the contamination has disappeared.

Contaminated contact cleaner should be regarded as chemical waste.

Only switch on the electrical installation after evaporation of the solvent (minimum of 15 minutes).

## Benefits

- Non conductive
- Leaves no residue
- Non corrosive
- Powerful jetspray
- High dissolving properties
- Leaves no residue
- Non-conductive
- Non-corrosive
- 360° valve

## Typical Properties

Contact Cleaner	
Contents	400 ml
Basis	Aliphatic Hydrocarbons with alcohol
Propellant	Carbondioxide
VOC-content	Approximately 97% w/w
Colour	Transparent
Scent	Characteristic
Relative density at 20°C	0.73 g/ml
Yield	3.8 g/sec
Refractive Index at 20°C	1.370
Vapour pressure at 20°C	5.5 to 6.5 bar

