

APOLLO C3 LL

FULL SYNTHETIC LONG LIFE ENGINE OIL

Description

Apollo C3 LL is a synthetic engine oil suitable for use in gasoline-, LPG- en diesel engines, with and without turbo, and also those equipped with an after treatment system (diesel particle filter for Euro IV). This oil is developed in particular for passenger cars and vans manufactured by the VAG-group (Volkswagen, Audi, Seat and Skoda) and is suitable for extended drain intervals (up till 30.000 km for gasoline- and up till 50.000 km for diesel engines).

This full synthetic lubricant guarantees a rapid build-up of a stable oil film at cold start, that remains stable at high operating temperatures, while friction is reduced in order to provide fuel economy.

Apollo C3 LL is developed with a special additive technology, which contains less phosphorus, sulphur and sulphated ash, in order to prevent the after treatment system (particle filter and catalysts) from blocking. Next to this, this oil provides an excellent oxidation stability and wear protection in order to provide maximum protection during long drain intervals.

Apollo C3 LL has been developed to meet the VW specifications 504.00 and 507.00, but can also be used in engines where older specifications are prescribed (VW 503.00, 506.00, 506.01, 505.01, 502.00, 500.00, 501.01 and 505.00). This oil is not suitable for R5 and V10 diesel engines.

Benefits

- Lower fuel consumption
- Very high Viscosity Index and a high resistance against shearing
- Fast cold start properties which results in less wear due to a stable lubricant film
- Great dispersant and detergent properties, which warrants a clean operation
- Very good lubrication film at very high working temperatures
- Very good Anti-Wear, Anti-Corrosion and Anti-Foam properties



Performance level

- ACEA C3
- VW 504.00/507.00
- BMW LL-04
- MB 229.51
- Porsche C30

Typical Properties

SAE		5W/30
Density 15 °C	kg/m ³	847
Viscosity 40 °C	St	72.0
Viscosity 100 °C	cSt	11.7
Viscosity CCS -30°C	cP	<6600
Viscosity Index		158
Pour point	°C	-42
Flash point C.O.C.	°C	210
TBN	mg KOH/g	6.6
Sulphated Ash	%wt	0.68
Operating temperature	°C	-35/150