

LINDAX MP

MULTI PURPOSE LITHIUM GREASE

Description

Grease Lithium MP are premium quality lithium soap thickened greases produced from low volatile high viscosity index mineral oils, superior fats/fatty acids, and a synergistic blend of additives and performance boosters.



Benefits

- Recommended for use in all general purpose industrial applications where grease lubrication is preferred.
- Provide optimum lubrication in bearings, sliding parts and mechanisms operating at moderate loads under ambient to medium temperatures up to 120°C.
- Can also be used as multipurpose wheel bearing and chassis greases in automotive applications.
- These greases are also suitable for lubrication of water pump bearings, machine tools, gears, couplings, and universal joints.

Typical Properties

	Lindax - MP 2	Lindax - MP 3
Appearance	Light Coloured Translucent	Light Coloured Translucent
NLGI No	2	3
Structure	Smooth	Smooth
Soap Type	Lithium 12 Hydroxystearate	Lithium 12 Hydroxystearate
Worked penetration, @25°C, 60/60 Strokes, mm-1	265-295	220-250
Base Oil viscosity, cSt @ 98.9°C	10-16	10-16
Drop Point°C, Min	180	180
Rust Test	Passes	Passes
Conforms to	Grade 2	Grade 3
Operating temperature, °C	-12/130	-20/130