

## GEVITRO GL-5 LS

### LIMITED SLIP GEAR OIL

#### Description

Gevitro GL-5 LS (Limited Slip) is recommended for passenger cars with "limited slip" differentials. Gevitro GL-5 LS is a high quality, hypoid type gear oil, specifically developed for limited slip differential units fitted to modern, high performance passenger cars and off-road leisure vehicles.

Gevitro GL-5 LS may be used in limited slip differentials of European, Japanese and American built vehicles, and is equally suitable in transmissions, gear axles, steering boxes and universal joints etc. Gevitro GL-5 LS is recommended for high performance passenger cars and sports cars frequently running at high speed and is equally suited in a wide range of applications where an EP-type gear oil is specified.

#### Benefits

- Optimizes frictional characteristics of the limited slip components
- Effective in reducing transmission noise
- Very good performance at high temperatures
- Gives maximum protection of the gears, bearings and limited-slip components



#### Performance levels

- API GL-5, MT-1
- MIL-L-2105D
- ZF TE-ML 05C/12C/16E
- Case MS 1317 (85W/140)

#### Typical Properties

SAE		80W/90	85W/140
Density 15 °C	kg/m <sup>3</sup>	890	900
Viscosity 100 °C	cSt	14.5	26.5
Viscosity Index		>95	>95
Pour Point	°C	>210	>230
Flash Point C.O.C	°C	-30	-18
Operating temperature	°C	-25/150	-15/150