

GEVITRO TDL FS

FULL SYNTHETIC TOTAL DRIVE LINE GEAR OIL

Description

Gevitro TDL FS is a fully synthetic premium Total Drive Line gear oil suitable for use where an API GL-3, 4 or 5 is recommended. It can be used in conventional but also modern gear boxes and rear axle differentials of passenger cars, trucks or buses, under lighter or very Heavy Duty conditions.

This lubricant is NOT suitable for use in Limited Slip Applications

Benefits

- Fully compatible with synchromesh gearboxes
- Excellent shifting performance in all temperature conditions, for a perfect all-seasons coverage
- Optimum resistance against wear, corrosion and foam building
- Very high oxidation and thermal stability
- Fuel Economy

Performance levels

- API GL-4/5
- SAE J2360
- MIL-PRF-2105E
- MAN 3343S/341 E2
- ZF TE-ML 02B/05A/07A/12E/16B/C/D/17B/19B/21A
- SCANIA STO 1:0
- MB 235.0
- Mack GO-J



Typical Properties

SAE		75W/90
Density 15 °C	kg/m3	878
Viscosity 40 °C		94.2
Viscosity 100 °C	cSt	15.2
Viscosity Index		171
Pour Point	°C	-36
Flash Point C.O.C	°C	200
Operating temperature	°C	-33/150