

GEVITRO TDL

TOTAL DRIVE LINE GEAR OIL

Description

Gevitro TDL is a premium Total Drive Line gear oil suitable for use where an API GL-3, 4 or 5 is recommended. It can be used in conventional but also modern gear boxes and rear axle differentials of passenger cars, trucks or buses, under lighter or very Heavy Duty conditions.

This lubricant is NOT suitable for use in Limited Slip Applications

Benefits

- Optimum protection of synchronizers and gears in the entire driveline
- Excellent resistance against wear, corrosion and foam building.
- Very high oxidation and thermal stability.
- Splendid performance in all temperature conditions, for a perfect all-seasons coverage.
- Fuel Economy



Performance levels

- API GL-3/4/5/MT-1
- SAE J2360
- MIL-PRF-2105E
- MAN 342 Type M2, MAN 341 Type E2/Z2
- ZF TE-ML 02B/05A/07A/08/12E/16B/16C/16D/17B/19B/21A
- Scania STO 1:0
- Volvo 97310
- MB 235.0
- Mack GO-J

Typical Properties

SAE		80W/90
Density 15 °C	kg/m ³	892
Viscosity 40 °C	cSt	148.0
Viscosity 100 °C	cSt	15.2
Viscosity Index		101
Pour Point	°C	-30
Flash Point C.O.C	°C	206
Operating temperature	°C	-25/150