

STYX STOU SS

SEMI SYNTHETIC UNIVERSAL TRACTOR OIL

Description

The lubrication of gasoline- and (turbocharged) diesel engines, transmissions, hydraulic installations and wet brakes.

Benefits

- High level of detergency and dispersancy
- Excellent "Extreme Pressure" properties
- Excellent resistance against oxidation
- Very good protection against wear

Typical Properties

SAE		10W/40
Density 15 °C	kg/m ³	874
Viscosity 40 °C	cSt	94.7
Viscosity 100 °C	cSt	14.5
Viscosity CCS -25 °C	cP	<7000
Viscosity Index		159
Pour Point	°C	-36
Flash Point C.O.C	°C	212
TBN	mg KOH/g	10.7
Operating Temperature	°C	-30/150



Performance levels

Engine Applications

- API CF-4/SF
- ACEA E3

Transmission Applications

- API GL-4/GL-5 Low Speed/High Torque
- John Deere JDM J20C
- MF 1139/1144
- Allison C-4
- ZF TE ML 06A/B/C/07B
- Caterpillar TO-2
- MIL-L-2104D/2105

Multipurpose Applications

- MB 227.1
- Ford M2C 159B/C, 134D
- Ford New Holland 82009202
- John Deere JDM J27